

Welcome

Managing HVAC in High Performance Buildings



EEBATM



HIGH PERFORMANCE
HOME SUMMIT 2019

OCTOBER 1-3 \ DENVER, CO


Hello my name is....

- Performance Construction Manager, Mitsubishi Electric Trane HVAC
- Former Director of Construction, Habitat for Humanity of Catawba Valley
- Former Sustainable Building Specialist, Habitat for Humanity International
- Licensed General Contractor
- HERS Rater
- EEBA Board Member



Performance Construction Team

- Chad Gillespie, Senior Manager
- Rob Howard, Southeast Regional Mgr
 - Scott Simmons, Virginia
 - David Paschall, Georgia
- Mike Schaefer, Central
- Kimberly Llewellyn, Southwest
- Shawn LeMons, Colorado
- Ken Johnson, California
- Greg Davenport, Northwest



Performance Construction Priorities

- Comfort
 - Individual room control
 - Quiet operation
- Health
 - Ductless (or less duct)
 - Filtration
 - Ventilation
 - Dehumidification
- Efficiency
 - Variable Refrigerant Flow
 - Inverter compressor




Performance Construction Goals

- Energy code compliance
- ERI performance path
- HERS score












Climates	2015 IECC HERS Index Scores
Zone 1 — 2	52
Zone 3	51
Zone 4	54
Zone 5	55
Zone 6	54
Zone 7 — 8	53




Performance Construction Goals

- Certification Programs
 - ENERGY STAR
 - EPA Indoor airPLUS
 - DOE Zero Energy Ready
 - Passive House
 - Net-Zero

						Source Zero Renewable Energy System
					Balanced Ventilation HRV/ERV	Balanced Ventilation HRV/ERV
				SOLAR READY Depends on climate	SOLAR READY ALWAYS	SOLAR READY ALWAYS
				Eff. Comps. & H ₂ O Distrib	Eff. Comps. & H ₂ O Distrib	Eff. Comps. & H ₂ O Distrib
				 EPA Indoor Air Package	 EPA Indoor Air Package	 EPA Indoor Air Package
				Ducts in Condit. Space	Ducts in Condit. Space	Ducts in Condit. Space
		HVAC QI w/WHV	HVAC QI w/WHV	HVAC QI w/WHV	Micro-load HVAC QI	Micro-load HVAC QI
		Water Management	Water Management	Water Management	Water Management	Water Management
		Independent Verification	Independent Verification	Independent Verification	Independent Verification	Independent Verification
IECC 2009 Enclosure	IECC 2012 Enclosure	IECC 2009 Enclosure	IECC 2012 Enclosure	IECC 2012/15 Encl./ES Win.	Ultra-Efficient Enclosure	Ultra-Efficient Enclosure
HERS 85-90	HERS 70-80	HERS 65-75	HERS 55-65	HERS 48-55	HERS 35-45	HERS < 0
 IECC 2009	 IECC 2012	 ENERGY STAR v3	ENERGY STAR v3.1	 ZERH	 PHIUS+ PHIUS+	 PHIUS+ SourceZero


Performance Construction Process

- Design
 - Do the math!
- Build
 - Quality installation
- Perform
 - Commission
 - Monitor
 - Maintain




Changes impacting HVAC Design

- Energy Codes
 - All new homes are tighter and better insulated
 - Mechanical ventilation is now required
 - How do we deal with ventilation loads?
- Load Profiles
 - Peak Loads vs Partial Loads
 - Sensible Heat Ratios
 - Equipment Selection
- Climate
 - Is the weather data in our energy models accurate?




Good News: some things have not changed



Residential HVAC Design Process

- Manual J
- Manual S
- Manual D
- Manual T
- Manual DHP?
- Manual LLH



Low Load Homes

- High Performance Homes have extremely low *sensible* loads (1000-1500 square feet/ton)
- Latent loads remain fairly constant
- Partial load runtime has increased
- HVAC equipment selection is more difficult
- Mechanical ventilation is now required
- How do we handle the ventilation load?
- Supplemental dehumidification may be required



Issues With Oversizing

- What is the problem with oversized HVAC equipment?





Photo courtesy of Energy Vanguard




HVAC Design Without Borders

- Tear Down the Walls
- Interior walls divide us and make HVAC design really challenging



Designing with Ductless

- Room by room load calculation
- Creating comfort zones
- What about small bedrooms and bathrooms?



Ductless Options

- Floor mount
- Wall mount
- Ceiling mount



**MLZ SERIES
ONE-WAY
CEILING CASSETTE**

**MITSUBISHI
ELECTRIC**
COOLING & HEATING

FITS BETWEEN 16" JOISTS



Earn a \$50 SPIFF
for each MLZ included on
an applicable job!

- ▶ NOW available as a 1:1 connection
- ▶ Available capacities in kBtu/h: 9, 12, 18
- ▶ Built-in condensate lift mechanism (21")
- ▶ Flexible air flow direction: left/right and up/down
- ▶ Four fan speeds plus Auto mode

For more information please contact your local distributor.

© 2018 Mitsubishi Electric Trade HVAC US LLC. All rights reserved.

**MITSUBISHI
ELECTRIC**
COOLING & HEATING

**PERFORMANCE
BUILDER**

Air Distribution Strategies

- Exhaust fans (-)
- Transfer fans (+)
- Inline fans (+)



Mechanical Ventilation

- Exhaust fans (-)
- Supply fans (+)
- ERV or HRV (+/-)



Whole House Filtration

- MERV 13 or HEPA
- 150-240 CFM Fan
- Supply and Return



Horizontal Ducted

- Low static (SEZ)
- Mid static (PEAD)



AIR HANDLER



SVZ 12-18

MVZ 12-36

PVA 12-42

CEILING MOUNT



SLZ 9-15

MLZ 9-42

PLA 12-42

PCA 12-42

FLOOR MOUNT



KJ 9-18

HORIZONTAL DUCTED



SEZ 9-18

PEAD 12-42

CONTROLS



Wireless
Sensor



kumo station™



BACnet/Modbus



Thermostat
Adapter



Wired and Wireless Controllers

WALL MOUNT



HM 9-24

GL 9-24

D 30-36

EF 9-18

FH 6-24

PKA 12-36

SINGLE-ZONE



COOLING ONLY
STANDARD HP
HYPER-HEATING



MULTI-ZONE



COOLING ONLY
STANDARD HP
HYPER-HEATING



BRANCH BOX



3 & 5 ZONE

mylinkdrive.com



Diamond System Builder

Indoor Units: 1 / 1 to 1
 Capacity: 12 / 6 to 12 (100.0%)
 * Connectable capacity is not actual capacity.
 Total Pipe Length: 32.9 / 65.0 feet

Correction Factors

Temperature: 0.97 1.00
 Piping Length: 0.98 0.99
 Defrosting: - 1.00
 User Derate: 1.00 1.00

Total Derate: 0.95 0.99

Additional Refrigerant: 0.1 lb

Total Refrigerant Amount: 2.7 lb


Conditions (°F)

Cooling

Indoor DB 75.0 Humidity 59.0% Indoor WB 64.9
 Outdoor DB 97.0

Heating

Indoor DB 70.0
 Outdoor DB 9.0 Humidity 50.0% Outdoor WB 6.9



Pipe Dia. Liquid / Gas	Model Number	Clg.Total (Sens.)
Pipe Length (Elbows)	Group / Room / Tag Ref.	Htg.Total

11,350 BTU/h (8,501 BTU/h)
 13,521 BTU/h

Diamond System Builder

Indoor Units:	3 / 2 to 3
Capacity:	30 / 15 to 30
* Connectable capacity is not actual capacity.	
Total Pipe Length:	100.0 / 230.0 feet
Furthest Actual:	40.0 / 82.0 feet
Furthest Equiv.:	40.0 / 82.0 feet

Correction Factors

Outdoor Unit Capacity:	1.00	1.00
Temperature:	0.97	0.99
Piping Length:	0.99	1.00
Defrosting:	-	0.95
User Derate:	1.00	1.00

Total Derate:	0.96	0.94
Additional Refrigerant:	0.0	lb
Total Refrigerant Amount:	8.8	lb


Conditions (°F)

Cooling

Indoor DB	75.0	Humidity	59.0%	Indoor WB	64.9
Outdoor DB	95.0				


Heating

Indoor DB	70.0				
Outdoor DB	21.0	Humidity	72.8%	Outdoor WB	19.3




Comfort Zones

- Main Level



Comfort Zones

- Second Floor




Zoned Comfort Solutions

- Customized comfort
- Healthy Indoor Air Quality
- Multiple points of filtration
- Mechanical ventilation
- Moisture management
- Controls integration
- Energy efficiency for lower utility bills



Performance Builder Program

- Loyalty program for builders including:
 - Training and technical assistance
 - Marketing support (case studies, spotlight videos)
 - Equipment discounts and rebates
 - Model home program
 - Extended warranty program



Performance Contractors Wanted

- We are seeking Performance Contractors for design, installation, and commissioning of Zoned Comfort Solutions in high performance homes
- Our team will provide the training and technical support to help you succeed



WE BUILD BETTER
TO MAXIMIZE COMFORT, HEALTH, AND EFFICIENCY

COMFORT

Unlike conventional central systems, our Zoned Comfort Solutions™ provide individual cooling and heating to each zone. This means better airflow distribution and balance, greater temperature and moisture control, and the ultimate in personalized comfort.

↓67°
optimal sleeping temperature is below 67 degrees

HEALTH

Conventional central systems force a large volume of air through long duct runs and one main filter. Our Zoned Comfort Solutions offer smaller air handlers for each zone which also means multiple points of filtration. Room air circulates constantly while filters capture allergens. Units are extremely quiet which contributes to a more tranquil space and healthier environment.

EFFICIENCY

Adding comfort zoning also adds efficiency, at least 40%. Our Zone Comfort Solutions allow homeowners to adjust the system's operation to match their busy lives. If they aren't home or only occupying one or two rooms at a time they can turn off the other rooms so they save money.

37%
less energy consumption


PARAGON
KANSAS CITY, MISSOURI

MITSUBISHI ELECTRIC
COOLING & HEATING



What's in it for builders?

- No ducts = no duct leakage + no duct testing
- Lower HERS scores
- Energy code compliance
- Certification goals
- Fewer call backs
- Happy customers



2019 Housing Innovation Awards

Habitat for Humanity of Catawba Valley
The Rudy Project | Hickory, NC | HabitatCatawbaValley.org

"A home that is not only affordable to purchase, but also affordable to own and operate." *Habitat for Humanity Catawba Valley*

PROJECT DATA	KEY FEATURES
<ul style="list-style-type: none"> Layout: 3 bdrm, 2 bath, 1 ft, 1,160 ft² Climate: IECC 4A, mixed-humid Completed: January 2019 Category: affordable 	<ul style="list-style-type: none"> Walls: 2x6 24" o.c. advanced framing; ladder blocking, open and insulated headers, R-26 total; 1" drywall, R-19 unfaced batts, 1" OSB sheathing, 1" taped rigid foam, 1x4 furring strips, 1" engineered wood lap siding. Roof: Gable roof; coated OSB sheathing, architectural asphalt shingles. Attic: Vented attic; 20" R-50 blown fiberglass; 24" raised heel trusses. Foundation: Unvented crawlspace, R-11 total; 2" rigid EPS on inside face of 8" CMU, rubberized waterproof coating, 12-mil reinforced polyethylene liner over dirt. Windows: Double-pane, argon-filled, low-e, vinyl single-hung frames, U=0.30, SHGC=0.22. Air Sealing: 2.5 ACH 50, drywall glued at top plate, sill seal. Ventilation: ERV, MERV 13 filters. HVAC: Ductless mini-split heat pump, 12.5 HSPF, 26.1 SEER, 1 indoor air handler, 1 outdoor compressor, dehumidifier in crawl. Hot Water: Heat pump water heater, 3.39 EF, 50-gal., compact plumbing design. Lighting: 100% LED, motion sensors on exterior lights. Appliances: ENERGY STAR refrigerator, dishwasher, clothes washer, and dehumidifier. Solar: Solar ready. Water Conservation: WaterSense-labeled fixtures and toilets. Energy Management System: Programmable thermostat. Other: 3-ft doors and hallways, low-VOC paint, Green Guard cabinets and flooring, passive radon vent, IBHS Fortified Home Bronze-level features.

CONTACT

Derek Ross
828-612-1435
Derek@habitatcatawba.org

Energy Efficiency & Renewable Energy

For more information on the DOE Zero Energy Ready Home program, go to <http://energy.gov/buildings/zero-energy-ready-home> or scan the QR code.

IBHS Fortified Home

Imery Group
Monroe Farmhouse | Monroe, GA | ImeryGroup.com

"Despite extremely energy-efficient design, there was no compromise on aesthetics and only a reasonable cost premium." *Home owner*

PROJECT DATA	KEY FEATURES
<ul style="list-style-type: none"> Layout: 3 bdrm, 3 bath, 1.5 ft, 1,863 ft² Climate: IECC 3A, mixed-humid Completed: October 2018 Category: custom buyer 	<ul style="list-style-type: none"> Walls: 2x4 24 in. o.c. staggered on 2x6 plates; advanced framing; R-24 total: 1/2" drywall, R-21 cellulose, R-3 taped coated OSB sheathing, 3/4" rigid rainscreen, fiber cement cladding. Roof: Gable roof; 1/2" drywall, taped coated OSB sheathing, flashing, 1x4 furring strips, standing seam metal roof, ENERGY STAR Cool Roof certified. Attic: Vented attic; 15.5" R-50 blown cellulose, 6" R-21 open-cell spray foam on rim bands and knee walls, 8" to 10" raised energy heels. Foundation: Raised slab 8" concrete-filled CMU stem wall, compacted dirt base, 4" #57 stone, 1" R-10 rigid foam under slab and on perimeter, poly taped at seams, 4" concrete slab. Windows: Triple-pane, argon-filled, low-e2, vinyl casement frames, U=0.39, SHGC=0.23. Air Sealing: 2.69 ACH 50. Ventilation: ERV with humidity sensor, MERV 8 filters, condensation sensors on both fans. HVAC: 3 ductless mini-split heat pumps to 1 outside compressor, 1 ducted mini-split to 2nd compressor shared with a split-system water heater, 10 HSPF, 20 SEER, dehumidifier. Hot Water: Prototype split-system 80 gal. heat pump water heater shares HVAC outdoor condenser, est. EF=3.5; compact plumbing with PEX piping. Lighting: 90% LED, 10% CFL, motion sensors and timers. Appliances: ENERGY STAR refrigerator, dishwasher, ceiling fans, and bath fans. Solar: 8.2-kW PV system; inverter can disconnect from grid, battery storage. Water Conservation: WaterSense-labeled fixtures, drought-resistant landscaping. Energy Management System: Internet connected appliances, HVAC, PV tracking. Other: Wider doors, zero thresholds in bathroom, low-to-no-VOC products.

CONTACT

Luis Imery
770-294-1014
luis@imerygroup.com

Energy Efficiency & Renewable Energy

For more information on the DOE Zero Energy Ready Home program, go to <http://energy.gov/buildings/zero-energy-ready-home> or scan the QR code.

IBHS Fortified Home

Deltec Homes
Bluegate Horizon | Mills River, NC | DeltecHomes.com

"We have absolutely loved this home... just walking through the house every day is a joy." *A Deltec home owner*

PROJECT DATA	KEY FEATURES
<ul style="list-style-type: none"> Layout: 3 bdrm, 2 bath, 1 ft, 1,759 ft² Climate: IECC 4A, mixed-humid Completed: February 2019 Category: custom for buyer 	<ul style="list-style-type: none"> Walls: 2x6 24" o.c. advanced framing, R-24 total: 1/2" drywall, 5.5" unfaced fiberglass batt, 1/2" plywood sheathing, 1" R-5 XPS, rigid foam, draining house wrap, fiber cement lap siding, wall panels built in factory powered by renewable energy. Roof: Vaulted asymmetrical roof with clerestory windows, 1/2" drywall, open web trusses at 24" o.c., 1/2" plywood sheathing, polyolefin underlayment, ENERGY STAR Cool Roof. Attic: Unvented, vaulted ceilings; 8" R-30 open-cell spray foam under roof decking. Foundation: Slab on grade; 2" R-10 XPS at slab edge; termite inspection gap. Windows: Double-pane, argon-filled, low-e3, fiberglass double-hung, U=0.27, SHGC=0.21. Air Sealing: 1.44 ACH 50. Ventilation: Independently ducted HRV also exhausts guest bath. HVAC: Combination ductless; mini-split heat pump, 10.7 HSPF, 17.45 SEER, 2 indoor air handlers; electric baseboard back-up, MERV 8 filters at return grills in bedrooms. Hot Water: Heat pump water heater, 3.69 EF, 50-gal.; push button recirculation pump. Lighting: 100% LED, daylighting. Appliances: ENERGY STAR refrigerator, dishwasher, clothes washer, and ceiling fans. Solar: 6.5-kW PV system. Water Conservation: EPA WaterSense fixtures and toilets; two 50-gal. rain barrels. Energy Management System: Wi-Fi-enabled thermostat remotely controls mini-splits; heat pump water heater, dishwasher, and range; PV monitoring system. Other: No-step entries, 3-ft doors, Zero-VOC interior paints and primers, Green Seal-labeled carpet, KCMA-certified cabinetry, Green Guard-labeled flooring.

CONTACT

Leigha Dickens
828-253-0483
ldickens@deltechomes.com

Energy Efficiency & Renewable Energy

For more information on the DOE Zero Energy Ready Home program, go to <http://energy.gov/buildings/zero-energy-ready-home> or scan the QR code.

IBHS Fortified Home



Thank you!

Rob Howard, Regional Manager, Performance Construction
rhoward@hvac.me.com

Save the dates for next year:

